

## Oak Ecoline 2-layers - 11x70mm



### WOOD/BOTANIC NAME

Oak / Quercus petrea Liebl.

### ORIGIN

Europe: Croatia, Poland, Romania

### CLASSIFICATION OF THE WOOD SPECIES ACCORDING: EN 13489.2018 (E)\*

Quality + Class:  Natura ▲  Rustica ■

### Prefinished Multilayers Elements with T&G

Thickness:11 mm \* Width: 170mm Length:490mm \*\*

Top layer: Hardwood 3,8mm\*  
Supporting layer: Birch plywood 7,2mm

\* All sizes above mentioned are considered as nominal value and in millimeters the tolerance is about ± 0,5mm.

### TREATMENTS AND FINISHINGS

- UNFINISHED SMOOTH SURFACE
- UNFINISHED BRUSHED SURFACE

### LACQUER

UV water based lacquered

### Gloss

10 (+/-5)

### INSTALLATION

To be glued on screed using a 2-components glue . Products are compatible with underfloor heating and cooling system

### CE Marked

In accordance to UNI EN 14342:2013

TIPO DI PROVA	VALORE RILEVATO	TIPO DI PROVA	VALORE RILEVATO
FIRE REACTION TESTS	CFL s1	HEAT RESISTANCE	0,078 K/W
FORMALDEHYDE EMISSION	E1 < 0,01 ppm	DENSITY	> 760 Kg/m <sup>3</sup>
CONTENTS OF PENTACHLOROPHENOL	< 5 ppm	BIODEGRADABILITY	Class 1

Warranty, within the meaning and for the purpose of European directive 44/99/CE and Italian Legislative decree n. 206/2018.

\* Detailed Rule of En 13489:2004 (E) is inside the BERTI PRICE LIST

\*\* Small percentage % in length are allowed

## Oak Ecoline 2-layers - 11x90/100mm



### WOOD/BOTANIC NAME

Oak / Quercus petrea Liebl.

### ORIGIN

Europe: Croatia, Poland, Romania

### CLASSIFICATION OF THE WOOD SPECIES ACCORDING: EN 13489.2018 (E)\*

Quality + Class:  Natura ▲  Rustica ■

### Prefinished Multilayers Elements with T&G

Thickness: 11 mm \* Width: 90/100mm Length: 500/1200mm \*\*

Top layer: Hardwood 3,8mm\*  
Supporting layer: Birch plywood 7,2mm

\* All sizes above mentioned are considered as nominal value and in millimeters the tolerance is about ± 0,5mm.

### TREATMENTS AND FINISHINGS

- UNFINISHED SMOOTH SURFACE
- UNFINISHED BRUSHED SURFACE

### LACQUER

UV water based lacquered

### Gloss

10 (+/-5)

### INSTALLATION

To be glued on screed using a 2-components glue . Products are compatible with underfloor heating and cooling system

### CE Marked

In accordance to UNI EN 14342:2013

TIPO DI PROVA	VALORE RILEVATO	TIPO DI PROVA	VALORE RILEVATO
FIRE REACTION TESTS	CFL s1	HEAT RESISTANCE	0,078 K/W
FORMALDEHYDE EMISSION	E1 < 0,01 ppm	DENSITY	> 760 Kg/m <sup>3</sup>
CONTENTS OF PENTACHLOROPHENOL	< 5 ppm	BIODEGRADABILITY	Class 1

Warranty, within the meaning and for the purpose of European directive 44/99/CE and Italian Legislative decree n. 206/2018.

\* Detailed Rule of En 13489:2004 (E) is inside the BERTI PRICE LIST

\*\* Small percentage % in length are allowed