

# Data Sheet **Rrred**

2-LAYERS WIDE PLANKS - 13mm



**WOOD / BOTANIC NAME:** Oak / Quercus petrea Liebl.  
**ORIGIN:** Europe: Croatia, Poland, Romania

*Designed and Made in Italy.*

WITH  
**BERTI**

## CLASSIFICATION OF THE WOOD SPECIES ACCORDING: EN 13489.2004 (E)\*

Quality + Class:  Natura  Rustica

### Pre-finished multilayers elements with T&G

Thickness: 13 mm / Width: 130 > 220mm / \*\*Random Lengths: 1000 > 2500 mm

\*Top Layer: solid hardwood 4 mm / Supporting Layer: birch plywood 9 mm

\*\* All sizes above mentioned are considered as nominal value and in millimeters the tolerance is about  $\pm 0,5$  mm

### TREATMENTS + FINISHINGS

Smooth surface, lacquered

### SURFACE

Bevelled on the 4 sides

### LAQUER

UV water based lacquered

### GLOSS

10 (+/-5)

### INSTALLATION

To be glued on screed using a 2-components glue or floating installation using a specific underlay and gluing the grooves. In case of presence of an underfloor heating and /or cooling system the installation must be glued in order to grant a better stability of the product and a better thermal conduction.

### CE MARKED

In accordance to UNI EN 14342:2005

### TYPE OF TEST

### VALUE

### TYPE OF TEST

### VALUE

Fire reaction

DFL s1

Heat resistance

0,093 K/W

Formaldehyde emission

E1 < 0,01 ppm

Density

> 760 KG/m<sup>3</sup>

Content of pentachlorophenol

< 5 ppm

Biodegradability

Class 1



Warranty, within the meaning and for the purpose of European directive 44/99/CE and Italian Legislative Decree n. 206/2005.

\*Detailed rule EN 13489:2004 (E) is inside the Diesel Living with Berti price list.

\*\*Small percentage % in length are allowed.

# Data Sheet **Rrred**

Pattern 90°/60°/45°

2-LAYERS - 13X120mm



WITH



**WOOD / BOTANIC NAME:** Oak / Quercus petrea Liebl.

**ORIGIN:** Europe: Croatia, Poland, Romania

*Designed and Made in Italy.*

## CLASSIFICATION OF THE WOOD SPECIES ACCORDING: EN 13489.2004 (E)\*

Quality + Class:  Natura  Rustica

### Pre-finished multilayers elements with T&G

Thickness: 13 mm / Width: 120mm / \*\*Random Lengths: 600 > 800 mm

\*Top Layer: solid hardwood 4 mm / Supporting Layer: birch plywood 9 mm

\*\* All sizes above mentioned are considered as nominal value and in millimeters the tolerance is about  $\pm 0,5$  mm

### TREATMENTS + FINISHINGS

Smooth surface, lacquered

### SURFACE

Bevelled on the 4 sides

### LAQUER

UV water based lacquered

### GLOSS

10 (+/-5)

### INSTALLATION

To be glued on screed using a 2-components glue or floating installation using a specific underlay and gluing the grooves. In case of presence of an underfloor heating and /or cooling system the installation must be glued in order to grant a better stability of the product and a better thermal conduction.

### CE MARKED

In accordance to UNI EN 14342:2005

### TYPE OF TEST

### VALUE

### TYPE OF TEST

### VALUE

Fire reaction

DFL s1

Heat resistance

0,093 K/W

Formaldehyde emission

E1 < 0,01 ppm

Density

> 760 KG/m<sup>3</sup>

Content of pentachlorophenol

< 5 ppm

Biodegradability

Class 1



Warranty, within the meaning and for the purpose of European directive 44/99/CE and Italian Legislative Decree n. 206/2005.

\*Detailed rule EN 13489:2004 (E) is inside the Diesel Living with Berti price list.

\*\*Small percentage % in length are allowed.